



TECHNICAL DATA

ANCHORING GEL

PRODUCT #635

PRODUCT DESCRIPTION

Anchoring Gel #635 is a multi-purpose, multi-use, 100% solids epoxy anchoring gel. This exclusive formulation is a non-sag, quick cure gel with extremely high finished mechanical strength.

Anchoring Gel #635 can be used in both vertical and horizontal applications.

ADVANTAGES

- Easy 1:1 Mix Ratio
- 0 VOC/No solvent odors
- Good working time, but fast cure time
- Easily mixed in attached static wand tube (included)
- Can be finished to a feather edge (smooth)
- Great for cracks as deep as 2 inches
- Complete cure in 30-45 minutes

LIMITATIONS

- Do not apply below 50° F
- Do not apply to damp, moist or wet surfaces
- Only available in gray

PACKAGING

Anchoring Gel #635 comes in a 300 x 300 ml cartridge, and one static wand mix nozzle. Storing the product in a temperature-controlled area will allow the product to flow easier.

Store product in a temperature-controlled area (60°F–80° F)

Note: Plural component caulk gun and additional static mix nozzles are available for purchase.

PRODUCT APPLICATION

- Clean out areas or cracks to be patched and remove all loose concrete, paint, and debris
- Unscrew locking nut cap and remove restrictor plug (keep the plug for future use)
- Attach the static wand mixing application tube to the nozzle, reapply locking nut
- Depressing the caulk gun, squeeze and dispose of the first material until the color is a uniform gray (dispose of uncured material in accordance with local and state regulations)
- Apply to crack, or patch by simply squeezing the caulk gun handle
- Strike off excess with a putty knife or drywall knife
- Any remaining material can be used again by unscrewing the static wand and re-applying restrictor plug and cap (once used, please dispose of the static wand mixing tube)
- Clean any tools used with solvent